

# C15C

IC-CUSHION      LPG  
 3000 / 3500 / 4000 lbs.  
 (1500 / 1800 / 2000 kg)

GEN2



## STANDARD SPECIFICATIONS

15/18/20sC

Manufacturer's Designation		C15CL	C18CL	C20sCL
Load Capacity / Rated Load	lbs(kg)	3000 (1500)	3500 (1800)	4000 (2000)
Height Overhead Guard	in(mm)	81.1 (2060)	81.1 (2060)	81.1 (2060)
Width	in(mm)	37.0 (940)	37.0 (940)	37.0 (940)
Right Angle Stack (add load length and clearance)	in(mm)	85.2 (2167)	87.2 (2215)	88.2 (2241)
Outside Turning Radius	in(mm)	70.5 (1792)	72.5 (1840)	73.5 (1866)
Travel speed loaded / unloaded	mph (kph)	10.4 / 10.5 (16.7 / 16.9)	10.4 / 10.5 (16.7 / 16.9)	10.4 / 10.5 (16.7 / 16.9)
Engine / Rated output per SAE J1349	HP(KW) @ rpm	Hyundai / 52 (38.8) @ 2650	Hyundai / 52 (38.8) @ 2650	Hyundai / 52 (38.8) @ 2650

## STANDARD FEATURES

**2.4 liter LPG engine • EPA compliant • Single speed powershift transmission • Isolated operators cell • OHG mounted headlights • Cowl mounted lever controls • Power steering & tilt steering wheel • CLARK safety seat • Open core radiator & high capacity cooling system • LED instrument display with audible alarms • Automatic engine shutdown feature • Front tie down points • Low fuel warning • 1 Year / 2,000 hour warranty on basic truck • 2 Year / 4,000 hour warranty on major components • 48" LBR, 41" Class II carriage, 42" forks**



For more information on this model and the full line of CLARK Forklifts, find you local CLARK Dealer at [www.clarkmhc.com](http://www.clarkmhc.com).