

C60

IC-PNEUMATIC LPG/DIESEL
 13,500 / 15,500 / 16,500 / 18,000 lbs.
 (6000 / 7000 / 7500 / 8000 kg)

GEN2



STANDARD SPECIFICATIONS

C60/70/75/80

Manufacturer's Designation		C60D	C70D	C80D	C60L	C70L	C75L
Load Capacity / Rated Load	lbs(kg)	13,500 (6000)	15,500 (7000)	18,000 (8000)	13,500 (6000)	15,500 (7000)	16,500 (7500)
Height Overhead Guard	in(mm)	93.3 (2370)	93.3 (2370)	93.3 (2370)	93.3 (2370)	93.3 (2370)	93.3 (2370)
Width	in(mm)	83.7 (2125)	83.7 (2125)	83.7 (2125)	83.7 (2125)	83.7 (2125)	83.7 (2125)
Right Angle Stack (add load length and clearance)	in(mm)	214.0 (5437)	215.2 (5467)	228.0 (5792)	214.0 (5437)	215.2 (5467)	215.2 (5467)
Outside Turning Radius	in(mm)	134.6 (3420)	135.8 (3450)	148.6 (3775)	134.6 (3420)	135.8 (3450)	135.8 (3450)
Travel speed loaded / unloaded	mph (kph)	18.2 (29.3) / 21.4 (34.4)	17.5 (28.1) / 20.9 (33.7)	17.0 (27.4) / 20.0 (32.2)	18.2 (29.3) / 19.5 (31.4)	18.0 (29.0) / 18.8 (30.2)	17.6 (28.3) / 18.4 (29.6)
Engine / Rated output per SAE J1349	HP(KW) @ rpm	Iveco / 99 (74) @ 2300	Iveco / 99 (74) @ 2300	Iveco / 99 (74) @ 2300	GM / 93 (69) @ 2400	GM / 93 (69) @ 2400	GM / 93 (69) @ 2400

STANDARD FEATURES

Available with 4.5 L Turbo Charged 100 HP Iveco Diesel Engine or 4.3 L V-6 GM LPG Engine • Fully Automatic “Smart Shift” Transmission • Spacious Operator Compartment • Fully Adjustable, Full Suspension Seat • Simple & Error Proof Parking Brake • Wet Disc Brakes on ALL Models • Rugged Upright and Carriage • “Built to Last”[®] Chassis • Optional Operator Cab



For more information on this model and the full line of CLARK Forklifts, find your local CLARK Dealer at www.clarkmhc.com.