

ECX

ELECTRIC 36/48 VOLT
COUNTERBALANCED FOUR-WHEEL
4000 / 5000 / 6000 / 6500 lbs. (2000 / 2500 / 3000 / 3000 kg)



STANDARD SPECIFICATIONS

20/25/30/32

| Manufacturer's Designation | | ECX 20 | ECX 25 | ECX 30 | ECX 32 |
|---|-----------|--------------------------|--------------------------|--------------------------|--------------------------|
| Load Capacity / Rated Load @ 24" LC | lbs(kg) | 4000 (2000) | 5000 (2500) | 6000 (3000) | 6500 (3000) |
| Height Overhead Guard | in(mm) | 88 (2235) | 88 (2235) | 88 (2235) | 88 (2235) |
| Width | in(mm) | 41.9 (1063) | 43.9 (1114) | 43.9 (1114) | 45.4 (1154) |
| Right Angle Stack (Add Load Length and Clearance) | in(mm) | 86.8 (2204) | 89.7 (2279) | 91.3 (2319) | 96.2 (2444) |
| Outside Turning Radius | in(mm) | 70.2 (1783) | 72.6 (1845) | 73.9 (1877) | 78.3 (1989) |
| Travel speed unloaded | mph (kph) | 9.2 (14.8) / 11.3 (18.2) | 9.1 (14.6) / 11.0 (17.7) | 8.7 (14.0) / 10.8 (17.4) | 8.0 (12.9) / 10.4 (16.7) |
| Power Unit | | 36 volt / 48 volt | 36 volt / 48 volt | 36 volt / 48 volt | 36 volt / 48 volt |

STANDARD FEATURES

100% AC Technology • Enclosed motors • Advanced thermal protection for all motors and controls • Quiet, non-polluting operation • Hydrostatic power steering • Hydraulic cushioning in lift mechanism • Adjustable steering pylon • Large instrument dash display • Variety of lights, alarms and other options are available



For more information on this model and the full line of CLARK Forklifts, find you local CLARK Dealer at www.clarkmhc.com.