

TMX

ELECTRIC 36/48 VOLT
COUNTERBALANCED THREE-WHEEL
2500 / 3000 / 3000 / 3500 / 4000 / 5000 lbs.
(1250 / 1500 / 1500 / 1750 / 1815 / 2270 kg)



STANDARD SPECIFICATIONS

12/15S/15/17/20/25

Manufacturer's Designation		TMX 12	TMX 15S	TMX 15	TMX 17	TMX 20	TMX 25
Load Capacity / Rated Load @ 24" LC	lbs(kg)	2500 (1250)	3000 (1500)	3000 (1500)	3500 (1750)	4000 (1815)	5000 (2270)
Height Overhead Guard	in(mm)	83 (2108)	83 (2108)	83 (2108)	83 (2108)	83 (2108)	83 (2108)
Width	in(mm)	40.25 (1022)	40.25 (1022)	40.25 (1022)	40.25 (1022)	40.25 (1022)	42.25 (1073)
Right Angle Stack (Add Load Length and Clearance)	in(mm)	67.8 (1722)	67.8 (1722)	74.2 (1885)	74.2 (1885)	74.2 (1885)	76.1 (1933)
Outside Turning Radius	in(mm)	53.4 (1356)	53.4 (1356)	59.8 (1519)	59.8 (1519)	59.8 (1519)	61.9 (1565)
Travel speed loaded & unloaded	mph (kph)	9.3 (15.0)	9.3 (15.0)	9.3 (15.0)	9.3 (15.0)	9.3 (15.0)	7.5 (12.0)
Power Unit	std.(optional)	36 volt (48 volt)	36 volt (48 volt)	36 volt (48 volt)	36 volt (48 volt)	36 volt (48 volt)	36 volt (48 volt)

STANDARD FEATURES

- 100% AC System
- Enclosed motors
- Advanced thermal protection for all motors and controls
- Compact maneuverability allows tight turning radius for use in narrow aisles and confined areas
- Non-polluting, quiet operation
- Responsive, pre-reduction disc brakes
- Hydrostatic power steering
- Best in class drawbar pull
- Variety of lights, alarms and other options are available



For more information on this model and the full line of CLARK Forklifts, find you local CLARK Dealer at www.clarkmhc.com.